



# 4-Port RS-422 / 485 USB to Serial Adapter



RS485 to USB Adapter Auto Transmit

Model No. **USB-4COMi-M**



A 4-Port RS-422, RS-485 adapter for serial communication that utilizes four external DIP switches for easy access to the signal used. Automatic transmit and receive control for 2-wire RS-485 half-duplex mode.

- Use your existing USB port to expand your serial communication.
- Self-powered, with one switching power adapter 5V 2A included.
- High-Speed Communication with 128 byte FIFO chip, works through heavy loads.
- Industrial-grade metal housing for rugged applications.

**Interested? [LEARN MORE](#) →**



[View more images here >](#)

## Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

☎ [1-727-209-1300](tel:1-727-209-1300) (Local) ✉ [expert@coolgear.com](mailto:expert@coolgear.com)



**We Speak Your Speak** - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

**We're Ready For Integration, Every Time.** - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

**Within every great machine, lives Coolgear.** - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

**Advanced Engineering** - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

# PRODUCT SPECIFICATIONS

Looking for product documentation?

[View CAD Models, Data sheet and Drawings here >](#)



<b>Power</b>	<b>Input Voltage</b>	+5V DC
<b>Compliance</b>	<b>Country of Origin</b>	Taiwan
	<b>Certifications</b>	<a href="#">CE</a> , <a href="#">FCC</a>
	<b>Color</b>	Black
<b>Physical Characteristics</b>	<b>Mounting Style</b>	Surface Mount
	<b>Ports</b>	4 Serial Ports
<b>Serial Attributes</b>	<b>Serial Standards</b>	RS422, RS485
<b>Software</b>	<b>OS Support</b>	Linux, Mac OSX, Win 10, Win 7, Win 8
<b>Environmental</b>	<b>Operating Temperature</b>	0C to 55C
<b>Hardware</b>	<b>Chipset</b>	FTDI
	<b>Connector</b>	DB9 Male w/ Nuts
	<b>Chip Model</b>	FT4232HL, MAX3089E
<b>Other Data</b>	<b>Warranty</b>	1 year from date of purchase
	<b>Weight</b>	2.2 lbs
	<b>Dimensions</b>	13.25 × 7.25 × 2.75 in

## Ready to Buy? Let's get to work!

[Purchase order](#) lets set you up.

[Online with Credit card](#) Orders shipped same day!

\*orders placed prior to 3:30pm EST

 [1-888-688-2188 \(Toll free\)](tel:1-888-688-2188)

 [sales@coolgear.com](mailto:sales@coolgear.com)