

4 Port USB 3.2 Gen 1 Mini High-Power Hub w/ Port Status LEDs



Industrial Grade | +5V DC Input | Surface Mountable | 5 Gbps | LED Indicators

Model No. USBG-4PminiH





- Super Fast Speeds: This USB hub is 3.2 Gen 1 compliant, ensuring super-fast 5Gbps data transfer speeds. It supports super speed, high speed and full speed which enables it to be compatible with USB 2.0 / 1.1.
- Small-Scale Quality: Housed in a compact steel chassis with built in mountable flanges, the 4-port hub is perfect for discreet installations in offices, labs, warehouses, heavy machinery, automation equipment, and other industrial applications.
- Check Your Ports' Status: Quickly check the status of each port individually with built in LED indicators.
- Upstream: 1 USB port, Micro Type B connector
- Downstream: 4 USB ports, Type A connectors
- Power Connector: DC Barrel 1.3mm ID × 3.5mm OD Center Pin Positive
- Mounting Options: Wall & Surface
- Supply Current: 900mA USB Bus Power for Each Downstream Port

Interested? LEARN MORE →

Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

1-727-209-1300 (Local) expert@coolgear.com



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS

Looking for product documentation?

View CAD Models, Data sheet and Drawings here >



Input Voltage +5V DC

Power Source AC Adapter Included, DC Barrel Jack 1.3mm ID × 3.5mm OD

Idle Consumption 10.77mA Bus Powered

Adapter Input Current 0.45A

Power Adapter Input Voltage 100~240V AC

Adapter Output Current 4A
Adapter Output Voltage 5V DC
External Power Required No

Per USB Port Current 900mA maximum

Country of Origin China
Compliance

Certifications REACH, RoHS

Color Black

Item Dimensions (L × W ×

4.80 × 1.70 × 0.80 in.

Physical

Characteristics Item Weight 0.238 lbs.

H)

Mounting Style Surface / Wall Mount

Ports 4 USB Ports

Material of Construction Steel

What's in the Box Package Contents Hub, Power Adapter, USB-A to Micro USB-B Cable

Software OS Support Win 7, Win 8, Win 10, Win 11, Linux, Mac OSX

Operating Temperature -5°C to 45°C (23°F to 113°F)

Environmental Storage Temperature -10°C to 60°C (14°F to 140°F)

Humidity 5% ~ 95% (non-condensing)

Product

Warranty 1 year from date of purchase

Chipset GL 3520

LED Indicators Port Status, Power

Downstream USB Ports 4 Type-A Female USB

Upstream USB Ports 1 Micro Type-B Female USB

Performance & Max Data Transfer Rate 5Gbps

Safety Over Current Protection Yes

USB Interface USB 3.2 Gen 1 **UPC** 736983900531

Other Data Series <u>WKS-UH (Workstation Series Hubs)</u>

Weight .700 lbs

Dimensions $7.75 \times 3 \times 2 \text{ in}$

Ready to Buy? Let's get to work!

Purchase order lets set you up.

1-888-688-2188 (Toll free)