



4-Port USB DB-9 Serial Adapter Solution



USB to RS232 Cable Windows 11

Model No. USBG-4X2FTDI



The USBG-4X2FTDI 4-Port USB DB-9 Serial Adapter is a rugged plastic USB to Serial adapter that allows you to add 4 RS-232 serial ports to your computer by connecting to a single available USB port. There are no IRQ & COM port conflicts during install.

- USB host extends to 4 USB to RS232 5ft. cable ports giving additional COM's to work with.
- Installs as a standard Windows COM port with no system conflicts.
- Takes advantage of High-Speed communication with FTDI Drivers.
- DB9 Male serial ports connectors have screw lock security for safe connections.

Interested? [LEARN MORE](#) →



[View more images here >](#)

Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

☎ [1-727-209-1300](tel:1-727-209-1300) (Local) ✉ expert@coolgear.com



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS

Looking for product documentation?
[View CAD Models, Data sheet and Drawings here >](#)




Compliance	Country of Origin	China
Physical Characteristics	Color	Black
	Length	5ft
	Ports	4 Serial Ports
	Material of Construction	Plastic
	Screw Lock Compatible	Yes
	RS Signals	TxD, RxD, RTS, CTS, DSR, DTR, DCD, RI, GND
	Serial Standards	RS232
	Baud Rate	921.6K bps
	FIFO Receive	384 bytes
	FIFO Transmit	128 bytes
Serial Attributes	Data Bits	5, 6, 7, 8
	Parity	None, Even, Odd, Mark, Space
	Stop Bits	1, 1.5, 2
	Flow Control	Hardware (RTS, CTS), XON/XOFF
	OS Support	Win 11, Linux, Mac OSX, Win 10, Win 7, Win 8
	Operating Temperature	0°C to 55°C (32°F to 131°F)
	Storage Temperature	-20 to 75°C (-4 to 167°F)
Environmental	Humidity	5% ~ 95% (non-condensing)
Product Information	Warranty	1 year from date of purchase
Hardware	Chipset	FTDI
	LED Indicators	Power, TX / RX
	Connector	DB9 Male with Screws
	Warranty	1 year from date of purchase
Other Data	USB Interface	USB 2.0
	Weight	.6 lbs
	Dimensions	7 × 5.25 × 1.5 in

Ready to Buy? Let's get to work!

[Purchase order](#) lets set you up.

[Online with Credit card](#) Orders shipped same day!

*orders placed prior to 3:30pm EST

 [1-888-688-2188 \(Toll free\)](tel:1-888-688-2188)

 sales@coolgear.com