

7 Port USB 3.2 Gen 1 Hub PCBA w/ 15KV ESD Surge Protection & Port Status LEDs



+7~24V DC Input | 5 Gbps

Model No. CG-7PU31HB-PCBA



- Protect Your Equipment: The 7-port hub supports 15KV
 ESD surge protection for each port to keep your connected peripherals safe from harm.
- Super Fast Speeds: This USB hub is 3.2 Gen 1 compliant, ensuring super-fast 5Gbps data transfer speeds. It supports super speed, high speed and full speed which enables it to be compatible with 2.0 / 1.1.
- Upstream: 1 USB port, Type B connector
- **Downstream:** 7 USB ports, Type A connectors
- Power Connector: 2-Pin Terminal Block, DC Barrel 2.5mm
 ID × 5.5mm OD
- LED Indicators: 7 LEDs for each downstream port to indicate the current bus

Interested? LEARN MORE →





Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

¹ 1-727-209-1300 (Local) **expert@coolgear.com**



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS

Looking for product documentation?

View CAD Models, Data sheet and Drawings here >



Input Voltage +7~24V DC

2-Pin Terminal Block, AC Adapter Not Included, DC Barrel **Power Source**

Jack 2.5mm ID × 5.5mm OD

Idle Consumption 37.67mA Bus Powered, 68.2mA @ 12V Terminal Power **Power**

External Power Required No

Charging Downstream Port (CDP), Dedicated Charging Port **Charging Protocols**

Per USB Port Current 1.5 A

Country of Origin Taiwan Compliance

Certifications REACH, TAA Hubs, RoHS

Item Dimensions (L × W ×

 $6.03 \times 2.34 \times 1.05$ in.

H) **Physical**

Characteristics **Item Weight** 0.04 lbs.

> 7 USB Ports **Ports**

Software OS Support Win 11, Linux, Mac OSX, Win 10, Win 7, Win 8

Operating Temperature 0°C to 55°C (32°F to 131°F)

-20 to 75°C (-4 to 167°F) **Environmental Storage Temperature**

> Humidity 5% ~ 95% (non-condensing)

Product

Warranty 1 year from date of purchase **Information**

> Chipset GL 3522

Charging Downstream Port (CDP), Dedicated Charging Port **Charging Protocols**

(DCP)

Hardware LED Indicators Port Status, Power

> **Downstream USB Ports** 7 Type-A Female USB **Upstream USB Ports** 1 Type-B Female USB

ESD Protection 15KV Surge Protection for Each Port

Performance &

Other Data

Max Data Transfer Rate 5Gbps Safety

Over Current Protection Yes

Isolated/Surge Protected Yes

Over Voltage Protection Yes per buck

USB Interface USB 3.2 Gen 1

2-Pin Terminal Block, USB 3.0 Type-B Female, USB Type-A Connector

Female

UPC 045079163546

> Weight 0.1375 lbs **Dimensions** $7 \times 4.75 \times 0.8 \text{ in}$

Ready to Buy? Let's get to work!

Purchase order lets set you up.

¹ 1-888-688-2188 (Toll free)

Online with Credit card Orders shipped same day!

*orders placed prior to 3:30pm EST

*orders placed prior to 3:30pm EST