

7 Port USB 3.2 Gen 1 Hub w/ Surge Protection & Screw-Locking Ports



Industrial Grade | +7~24V DC Input | Surge Protection | Surface Mountable | DIN Rail | 5 Gbps | Screw Lock

Model No. USBG-7U3ML





- Protect Your Equipment: The 7-port USB 3.2 Gen 1 features 350 Watts of surge protection to keep your connected peripherals safe from harm.
- Super Fast Speeds: This USB hub is 3.2 Gen 1 compliant, ensuring super-fast 5Gbps data transfer speeds. It supports super speed, high speed and full speed which enables it to be compatible with USB 2.0 / 1.1.
- Superior Build Quality: Housed in a rugged steel chassis with built in mountable flanges, the 7-port hub is perfect for installations in offices, labs, warehouses, heavy machinery, automation equipment, and other industrial applications.
- Upstream: 1 USB port, Type B connector, Screw-lock type
- Downstream: 7 USB ports, Type A connectors, Screw-lock type
- Power Connector: 2-Pin Terminal Block
- Mounting Options: Wall, Surface, and DIN Rail
- **Supply Current:** 1.5A USB Bus Power for Each Downstream Port

Interested? LEARN MORE >

Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

1-727-209-1300 (Local) expert@coolgear.com



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS

Looking for product documentation?

View CAD Models, Data sheet and Drawings here >



Input Voltage +7~24V DC

Power Source 2-Pin Terminal Block, AC Adapter Not Included

50W

Max Wattage Power

> Apple 2.4A, Charging Downstream Port (CDP), Dedicated **Charging Protocols**

Charging Port (DCP)

Per USB Port Current 1.5 Amp

Country of Origin Taiwan Compliance

Certifications REACH, RoHS

Black Color

Item Dimensions (L × W ×

 $6.37 \times 2.60 \times 1.42$ in.

Item Weight 0.775 lbs. **Physical**

Characteristics Surface / Wall Mount, Din-Rail Mount **Mounting Style**

> **Ports** 7 USB Ports Material of Construction Galvanized Steel

Screw Lock Compatible Yes

2-Pin Terminal Block, DIN Rail Clip(s), Hub, Screw Lock USB-A What's in the Box Package Contents

to Screw Lock USB-B Cable, Screw Pack

Win 11, Linux, Mac OSX, Win 10, Win 7, Win 8 **Software OS Support**

> **Operating Temperature** 0°C to 55°C (32°F to 131°F)

Environmental Storage Temperature -20°C to 85°C (-4°F to 185°F)

> **Humidity** 5% ~ 95% (non-condensing)

Product

Warranty 1 year from date of purchase **Information**

> Chipset GL 3523

Apple 2.4A, Charging Downstream Port (CDP), Dedicated **Charging Protocols**

Charging Port (DCP)

Hardware

LED Indicators Power

Downstream USB Ports 7 Type-A Female USB **Upstream USB Ports** 1 Type-B Female USB

Performance &

Max Data Transfer Rate 5Gbps Safety **Surge Protection** 350W

> **USB** Interface USB 3.2 Gen 1 **UPC** 729440691479

DRS-UH (DIN-Rail Series Hubs) **Other Data Series**

> Weight 1.200 lbs

Dimensions $11.25 \times 6.25 \times 2.00$ in

Ready to Buy? Let's get to work!

Purchase order lets set you up.

1-888-688-2188 (Toll free)

Online with Credit card Orders shipped same day!

*orders placed prior to 3:30pm EST

*orders placed prior to 3:30pm EST