

7 Port USB 3.2 Gen 1 Hub w/ Surge Protection & Screw-Locking Ports



Industrial Grade | +7~24V DC Input | Surge Protection | Surface Mountable | DIN Rail | 5 Gbps | Screw Lock

Model No. USBG-7U3ML



- **Protect Your Equipment:** The 7-port USB 3.2 Gen 1 features 350 Watts of surge protection to keep your connected peripherals safe from harm.
- Super Fast Speeds: This USB hub is 3.2 Gen 1 compliant, ensuring super-fast 5Gbps data transfer speeds. It supports super speed, high speed and full speed which enables it to be compatible with USB 2.0 / 1.1.
- **Superior Build Quality:** Housed in a rugged steel chassis with built in mountable flanges, the 7-port hub is perfect for installations in offices, labs, warehouses, heavy machinery, automation equipment, and other industrial applications.
- Upstream: 1 USB port, Type B connector, Screw-lock type
- Downstream: 7 USB ports, Type A connectors, Screw-lock type
- Power Connector: 2-Pin Terminal Block
- Mounting Options: Wall, Surface, and DIN Rail
- Supply Current: 1.5A USB Bus Power for Each Downstream Port

Interested? LEARN MORE +

Questions? Speak to an engineering expert today! Our on site engineers are ready to help you with your build.

1-727-209-1300 (Local) expert@coolgear.com



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solutionoriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us. We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS



	Input Voltage	+7~24V DC
	Power Source	2-Pin Terminal Block, AC Adapter Not Included
Power	Max Wattage	50W
	Charging Protocols	Apple 2.4A, Charging Downstream Port (CDP), Dedicated Charging Port (DCP)
Compliance	Per USB Port Current	1.5 Amp
	Country of Origin	Taiwan
	Certifications	REACH, RoHS
	Color	Black
	Item Dimensions (L × W × H)	6.37 × 2.60 × 1.42 in.
Physical	Item Weight	0.775 lbs.
Characteristics	Mounting Style	Surface / Wall Mount, Din-Rail Mount
	Ports	7 USB Ports
	Material of Construction	Galvanized Steel
	Screw Lock Compatible	Yes
What's in the Box	Package Contents	2-Pin Terminal Block, DIN Rail Clip(s), Hub, Screw Lock USB-A to Screw Lock USB-B Cable, Screw Pack
Software	OS Support	Win 11, Linux, Mac OSX, Win 10, Win 7, Win 8
	Operating Temperature	0°C to 55°C (32°F to 131°F)
Environmental	Storage Temperature	-20°C to 85°C (-4°F to 185°F)
	Humidity	5% ~ 95% (non-condensing)
Product Information	Warranty	1 year from date of purchase
	Chipset	GL 3523
Hardware	LED Indicators	Power
	Downstream USB Ports	7 Type-A Female USB
	Upstream USB Ports	1 Type-B Female USB
Performance &	Max Data Transfer Rate	5Gbps
Cafaty		
Safety	Surge Protection	350W
Salety	Surge Protection USB Interface	350W USB 3.2 Gen 1
Salety	-	
Other Data	USB Interface UPC Series	USB 3.2 Gen 1
	USB Interface UPC	USB 3.2 Gen 1 729440691479

Ready to Buy? Let's get to work!

Purchase order lets set you up.

Online with Credit card Orders shipped same day!

⁽ <u>1-888-688-2188 (Toll free)</u>

sales@coolgear.com