



Dual-Port RS-232 to Ethernet Data Gateway TCP/IP Industrial Metal Case



RS232 to Ethernet - Two Port Adapter

Model No. MSD-SRF2XM



The MSD-SRF2X Dual port RS-232 to Ethernet data gateway will address the need to add 2 RS-232C devices to an IP-based Ethernet LAN on your system, has built-in watch dog function for hardware hangs.

- Solution for connecting PLC's, Meters, and Sensors to an IP based Ethernet LAN.
- Uses RJ45 port connection for 10/100 Network.
- Provides a remote connection through IP addressing methods (UDP, IP, TCP, ICMP, HTTP, DHCP, ARP-Ping)
- Includes a built-in watch dog function designed to reset the MSD-SRF2XM when the hardware/software encounters an error.

Interested? [LEARN MORE](#) →



[View more images here >](#)

Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

☎ [1-727-209-1300](tel:1-727-209-1300) (Local) ✉ expert@coolgear.com



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS

Looking for product documentation?
[View CAD Models, Data sheet and Drawings here >](#)




Power	Input Voltage	+5V DC
Compliance	Country of Origin	Taiwan
	Certifications	CE , FCC
Physical Characteristics	Color	Black
	Mounting Style	Surface Mount
	Ports	2 Serial Ports
	Screw Lock Compatible	Yes
Serial Attributes	Serial Standards	RS232
	Baud Rate	115.2K bps
	OS Support	Win 7, Win 8, Win Vista, Win XP
Software	Operating Temperature	0C to 55C
Environmental	UPC	729440691783
	Connector	DB9 Male w/ Nuts, RJ45
Other Data	Chip Model	EM636165TS, S3C4510B01, ZT213LFEA
	Warranty	1 year from date of purchase
	Weight	1.1 lbs
	Dimensions	7.75 × 5 × 1.75 in

Ready to Buy? Let's get to work!

[Purchase order](#) lets set you up.

[Online with Credit card](#) Orders shipped same day!

*orders placed prior to 3:30pm EST

 [1-888-688-2188 \(Toll free\)](tel:1-888-688-2188)

 sales@coolgear.com