



Dual-Port RS-232 to Ethernet Data Gateway TCP/IP Industrial Metal Case



RS232 to Ethernet - Two Port Adapter

Model No. MSD-SRF2XM



The MSD-SRF2X Dual port RS-232 to Ethernet data gateway will address the need to add 2 RS-232C devices to an IP-based Ethernet LAN on your system, has built-in watch dog function for hardware hangs.

- Solution for connecting PLC's, Meters, and Sensors to an IP based Ethernet LAN.
- Uses RJ45 port connection for 10/100 Network.
- Provides a remote connection through IP addressing methods (UDP, IP, TCP, ICMP, HTTP, DHCP, ARP-Ping)
- Includes a built-in watch dog function designed to reset the MSD-SRF2XM when the hardware/software encounters an error.

Interested? [LEARN MORE](#) →



[View more images here >](#)

Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

☎ [1-727-209-1300](tel:1-727-209-1300) (Local) ✉ expert@coolgear.com



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS

Looking for product documentation?

[View CAD Models, Data sheet and Drawings here >](#)




Power	Input Voltage	+5V DC
Compliance	Country of Origin	Taiwan
	Certifications	CE , FCC
Physical Characteristics	Color	Black
	Mounting Style	Surface Mount
	Ports	2 Serial Ports
	Screw Lock Compatible	Yes
Serial Attributes	Serial Standards	RS232
	Baud Rate	115.2K bps
	OS Support	Win XP, Win Vista, Win 7, Win 8
Software	Operating Temperature	0C to 55C
Environmental	UPC	729440691783
	Connector	DB9 Male w/ Nuts, RJ45
Other Data	Chip Model	EM636165TS, S3C4510B01, ZT213LFEA
	Warranty	1 year from date of purchase
	Weight	1.1 lbs
	Dimensions	7.75 × 5 × 1.75 in

Ready to Buy? Let's get to work!

[Purchase order](#) lets set you up.

[Online with Credit card](#) Orders shipped same day!

*orders placed prior to 3:30pm EST

 [1-888-688-2188 \(Toll free\)](tel:1-888-688-2188)

 sales@coolgear.com