

12 Port USB 2.0 Powered Hub w/ Port Status LEDs



Industrial Grade | +7~24V DC Input | Surface Mountable | 480 Mbps | LED Indicators

Model No. USBG-12U2ML



- **High Speeds:** This USB hub is 2.0 compliant, ensuring fast 480Mbps data transfer speeds. It supports high speed and full speed which enables it to be compatible with USB 1.1.
- Superior Build Quality: Housed in a rugged steel chassis with built in mountable flanges, the 12-port hub is perfect for installations in offices, labs, warehouses, heavy machinery, automation equipment, and other industrial applications.
- Check Your Ports' Status: Quickly check the status of each port individually with built in LED indicators.
- Upstream: 1 USB port, Type B connector
- **Downstream:** 12 USB ports, Type A connectors
- Power Connector: 3-Pin Terminal Block
- Mounting Options: Wall & Surface

Interested? LEARN MORE >







<u>View more</u> <u>images here ></u>

Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

¹ 1-727-209-1300 (Local) **expert@coolgear.com**



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS

Looking for product documentation?

View CAD Models, Data sheet and Drawings here >



Input Voltage +7~24V DC

Power Source 3-Pin Terminal Block, AC Adapter Not Included

Idle Consumption 23mA @ 12V Terminal Power

External Power Required Yes

Country of Origin Taiwan
Compliance

Certifications REACH, RoHS

Color Black

Item Dimensions (L × W ×

6.25 (5.250 w/flange) × 2.60 × 2.00 in.

Physical

Characteristics Item Weight 0.843 lbs.

H)

Mounting Style Surface / Wall Mount, Din-Rail Mount

Ports 12 USB Ports

Material of Construction Galvanized Steel

What's in the Box Package Contents

3-Pin Terminal Block, Hub, Mounting Plate, Screw Pack, USB-

A to USB-B Cable

Software OS Support Win 11, Linux, Mac OSX, Win 10, Win 7, Win 8

Operating Temperature 0°C to 55°C (32°F to 131°F)

Environmental Storage Temperature -20°C to 85°C (-4°F to 185°F)

Humidity 5% ~ 95% (non-condensing)

Product

Warranty 1 year from date of purchase

Chipset GL 852G

LED Indicators Port Status, Power

Downstream USB Ports 12 Type-A Female USB

Upstream USB Ports 1 Type-B Female USB

Performance & Max Data Transfer Rate 480Mbps

Safety Over Current Protection Yes

USB Interface USB 2.0

UPC 729440625146

Other Data Series <u>DRS-UH (DIN-Rail Series Hubs)</u>

Weight 1.2 lbs

Dimensions $8.5 \times 5.5 \times 2.25 \text{ in}$

Ready to Buy? Let's get to work!

Purchase order lets set you up.

Online with Credit card Orders shipped same day!

*orders placed prior to 3:30pm EST

1-888-688-2188 (Toll free)

sales@coolgear.com