

16 Port USB 2.0 Rack-Mountable Hub w/ Internal Power Supply, **ESD Surge Protection, & Port Status LEDs**



Industrial Grade | +110~220V AC Input | Surge Protection | Rack Mount | DIN Rail | 480 Mbps | Screw Lock

Model No. HUB-1600i-RM





- peripherals safe from harm. • High Speeds: This USB hub is 2.0 compliant, ensuring fast 480Mbps data transfer speeds. It supports high speed and full speed which enables it to be compatible with USB 1.1.
- Superior Build Quality: Housed in a rugged steel chassis, the 16-port hub is perfect for installations in offices, labs, warehouses, heavy machinery, automation equipment, and

• **Protect Your Equipment:** The 16-port USB 2.0 hub features 15kV ESD surge protection to keep your connected

- Upstream: 1 USB port, Type B connector, Screw-lock type
- **Downstream:** 16 USB ports, Type A connectors, Screw-lock
- Power Connector: 2-Pin Terminal Block, IEC C14 Connector
- Mounting Options: Rack, Wall, Surface, Desktop, & DIN Rail
- LED Indicators: Power & Port Status LEDs

other industrial applications.



Interested? LEARN MORE →

Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

1-727-209-1300 (Local)
 expert@coolgear.com



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solutionoriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us. We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This



PRODUCT SPECIFICATIONS

Looking for product documentation?

View CAD Models, Data sheet and Drawings here >



Input Voltage 100 – 240V AC

Power Source 2-Pin Terminal Block, AC Adapter Included, IEC C14

Idle Consumption 70mA @ AC Power

Adapter Input Voltage 90~264V AC

Power Adapter Output Current 500mA

Adapter Output Voltage 5V DC

External Power Required No

Overall Power Per USB

Port 5V per port

Per USB Port Current 500mA

Country of Origin Taiwan
Compliance

Certifications <u>CE, FCC, RoHS, TAA Hubs</u>

Color Black

Item Dimensions (L × W ×

16.81 × 5.67 × 1.73 in.

')

Item Weight Physical

Characteristics Mounting Style

Desktop, Surface Mount (Optional Brackets), Din-Rail

3.606 lbs.

(Optional Bracket), Rack Mount, Wall Mount

Ports 16 USB Ports

Material of Construction Galvanized Steel

Screw Lock Compatible Yes

2-Pin Terminal Block, Hub, Mounting Plate, Power Cable, Rack

What's in the Box Package Contents Mounting Flanges, Screw Pack, USB-A to Screw Lock USB-B

Cable

Software OS Support Win 7, Win 8, Win 10, Win 11, Linux, Mac OSX

Operating Temperature -40°C to 70°C (-40°F to 158°F)

Environmental Storage Temperature -20 to 75°C (-4 to 167°F)

Humidity 5% ~ 95% (non-condensing)

Product

Warranty 1 year from date of purchase

Chipset GL 852GT

LED Indicators Port Status, Power

Downstream USB Ports 16 Type-A Female USB **Upstream USB Ports** 1 Type-B Female USB

ESD Protection 15KV Surge Protection for Each Port

Performance &

Safety Max Data Transfer Rate 480Mbps

Isolated/Surge Protected Yes

Over Current Protection Yes

Supported Data Speed 480Mb/sec, 12Mb/sec, 1.5Mb/sec

USB Interface USB 2.0

UPC 729440691530

 Other Data
 Series

 RMS-UH (Rack Mount Series Hubs)

Weight 5.125 lbs Dimensions $23 \times 9 \times 2.5$ in

Ready to Buy? Let's get to work!

Purchase order lets set you up.

Online with Credit card Orders shipped same day!

*orders placed prior to 3:30pm EST

1-888-688-2188 (Toll free)

sales@coolgear.com