



4 Port USB 2.0 Powered Hub w/ Port Status LEDs



Industrial Grade | +7~24V DC Input | Surface Mountable | DIN Rail | 480 Mbps | LED Indicators

Model No. USBG-4U2ML



- **High Speeds:** This USB hub is 2.0 compliant, ensuring fast 480Mbps data transfer speeds. It supports high speed and full speed which enables it to be compatible with USB 1.1.
- **Superior Build Quality:** Housed in a rugged steel chassis with built in mountable flanges, the 4-port hub is perfect for installations in offices, labs, warehouses, heavy machinery, automation equipment, and other industrial applications.
- **Check Your Ports' Status:** Quickly check the status of each port individually with built in LED indicators.
- **Upstream:** 1 USB port, Type B connector
- **Downstream:** 4 USB ports, Type A connectors
- **Power Connector:** 2-Pin Terminal Block
- **Mounting Options:** Wall, Surface, and DIN Rail
- **Supply Current:** 900mA USB Bus Power for Each Downstream Port

Interested? [LEARN MORE](#) →



[View more images here >](#)

Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

☎ [1-727-209-1300](tel:1-727-209-1300) (Local) ✉ expert@coolgear.com



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS

Looking for product documentation?

[View CAD Models, Data sheet and Drawings here >](#)



Power	Input Voltage	+7~24V DC
	Power Source	3-Pin Terminal Block, AC Adapter Not Included
	Idle Consumption	14mA @ 12V Terminal Power, 18mA Bus powered
	External Power Required	No
	Charging Protocols	Dedicated Charging Port (DCP)
Compliance	Per USB Port Current	900mA maximum
	Certifications	TAA Hubs , CE , FCC , RoHS
Physical Characteristics	Color	Black
	Item Dimensions (L x W x H)	4.50 x 2.26 x 1.03 in.
	Item Weight	0.45 lbs.
	Mounting Style	Surface / Wall Mount, Din-Rail Mount
	Ports	4 USB Ports
What's in the Box	Material of Construction	Galvanized Steel
	Package Contents	DIN Rail Clip(s), Hub, Screw Pack, USB-A to USB-B Cable
Software	OS Support	Win 7, Win 8, Win 10, Win 11, Linux, Mac OSX
Environmental	Operating Temperature	0°C to 55°C (32°F to 131°F)
	Storage Temperature	-20°C to 85°C (-4°F to 185°F)
	Humidity	5% ~ 95% (non-condensing)
Product Information	Warranty	1 year from date of purchase
Hardware	Chipset	NEC D720114
	LED Indicators	Port Status, Power
	Downstream USB Ports	4 Type-A Female USB
	Upstream USB Ports	1 Type-B Female USB
Performance & Safety	Max Data Transfer Rate	480Mbps
	USB Interface	USB 2.0
	UPC	729440625122
Other Data	Series	DRS-UH (DIN-Rail Series Hubs)
	Weight	.85 lbs
	Dimensions	9 x 6.25 x 1.75 in

Ready to Buy? Let's get to work!

Purchase order lets set you up.

Online with Credit card Orders shipped same day!

*orders placed prior to 3:30pm EST

 **1-888-688-2188 (Toll free)**

 **sales@coolgear.com**