

4 Port USB 2.0 Powered Hub w/ Port Status LEDs



Industrial Grade | +7~24V DC Input | Surface Mountable | DIN Rail | 480 Mbps | LED Indicators

Model No. USBG-4U2ML



- **High Speeds:** This USB hub is 2.0 compliant, ensuring fast 480Mbps data transfer speeds. It supports high speed and full speed which enables it to be compatible with USB 1.1.
- Superior Build Quality: Housed in a rugged steel chassis with built in mountable flanges, the 4-port hub is perfect for installations in offices, labs, warehouses, heavy machinery, automation equipment, and other industrial applications.
- Check Your Ports' Status: Quickly check the status of each port individually with built in LED indicators.
- Upstream: 1 USB port, Type B connector
- **Downstream:** 4 USB ports, Type A connectors
- Power Connector: 2-Pin Terminal Block
- Mounting Options: Wall, Surface, and DIN Rail
- Supply Current: 900mA USB Bus Power for Each Downstream Port



Interested? LEARN MORE >

Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

¹ 1-727-209-1300 (Local) **expert@coolgear.com**



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS

Looking for product documentation?

View CAD Models, Data sheet and Drawings here >



Input Voltage +7~24V DC

Power Source 3-Pin Terminal Block, AC Adapter Not Included Idle Consumption 14mA @ 12V Terminal Power, 18mA Bus powered

Power External Power Required No

Charging Protocols Dedicated Charging Port (DCP)

Per USB Port Current 900mA maximum

Compliance Certifications TAA Hubs, CE, FCC, RoHS

Color Black

Item Dimensions (L × W ×

4.50 × 2.26 × 1.03 in.

Physical

Item Weight 0.45 lbs.

H)

Mounting Style Surface / Wall Mount, Din-Rail Mount

Ports 4 USB Ports

Material of Construction Galvanized Steel

What's in the Box Package Contents DIN Rail Clip(s), Hub, Screw Pack, USB-A to USB-B Cable

Software OS Support Win 11, Linux, Mac OSX, Win 10, Win 7, Win 8

Operating Temperature 0°C to 55°C (32°F to 131°F)

Environmental Storage Temperature -20°C to 85°C (-4°F to 185°F)

Humidity 5% ~ 95% (non-condensing)

Product

Warranty 1 year from date of purchase

Chipset NEC D720114

Charging Protocols Dedicated Charging Port (DCP)

Hardware LED Indicators Port Status, Power

Downstream USB Ports 4 Type-A Female USB **Upstream USB Ports** 1 Type-B Female USB

Performance &

Safety

Max Data Transfer Rate 480Mbps

USB Interface USB 2.0

UPC 729440625122

Other Data Series DRS-UH (DIN-Rail Series Hubs)

Weight .85 lbs

Dimensions $9 \times 6.25 \times 1.75 \text{ in}$

Ready to Buy? Let's get to work!

Purchase order lets set you up.

Online with Credit card Orders shipped same day!

*orders placed prior to 3:30pm EST

1-888-688-2188 (Toll free)

sales@coolgear.com