

# 4 Port USB 2.0 Powered Hub w/ Port Status LEDs & Screw Locking Ports



Industrial Grade | +5V DC Input | Surface Mountable | 480 Mbps | Screw Lock

Model No. USBG-4SU2MLA



- **High Speeds:** This USB hub is 2.0 compliant, ensuring fast 480Mbps data transfer speeds. It supports high speed and full speed which enables it to be compatible with USB 1.1.
- Superior Build Quality: Housed in a rugged steel chassis with built in mountable flanges, the 4-port hub is perfect for installations in offices, labs, warehouses, heavy machinery, automation equipment, and other industrial applications.
- Power Your Way: The 4-port hub works in either buspowered mode or self-powered mode with the included power adapter.
- Upstream: 1 USB port, Type B connector, Screw-lock type
- Downstream: 4 USB ports, Type A connectors, Screw-lock type
- Power Connector: DC Barrel Jack
- Mounting Options: Wall & Surface



Interested? LEARN MORE >

### **Questions?** Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

<sup>1</sup> 1-727-209-1300 (Local) **expert@coolgear.com** 



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

**Within every great machine, lives Coolgear.** - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

**Advanced Engineering** - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

#### **PRODUCT SPECIFICATIONS**

#### Looking for product documentation?

View CAD Models, Data sheet and Drawings here >



+5V DC **Input Voltage** 

**Power Source** AC Adapter Included, DC Barrel Jack 2.1mm ID x 5.5mm OD

**Idle Consumption** 21.5mA Bus Powered, 22mA @ 5V Barrel Power

**Adapter Input Current** 0.3A

100~240V AC **Adapter Input Voltage Power** 

> Adapter Output Current 2A Adapter Output Voltage 5V DC **External Power Required No**

Charging Downstream Port (CDP), Dedicated Charging Port **Charging Protocols** 

(DCP)

**Country of Origin Taiwan** Compliance

Certifications REACH, TAA Hubs, RoHS

Color Black

Item Dimensions (L × W ×

**Environmental** 

**Product** 

 $7.02 \times 2.34 \times 0.91$  in.

**Item Weight** 0.588 lbs. **Physical** 

Characteristics **Mounting Style** Surface / Wall Mount

> **Ports** 4 USB Ports Material of Construction Galvanized Steel

**Screw Lock Compatible** Yes

Hub, Power Adapter, USB-A to Screw Lock USB-B Cable, USB-What's in the Box Package Contents

A to USB-B Cable

**Software OS Support** Win 11, Linux, Mac OSX, Win 10, Win 7, Win 8

> 0°C to 55°C (32°F to 131°F) **Operating Temperature Storage Temperature** -20 to 75°C (-4 to 167°F)

> Humidity 5% ~ 95% (non-condensing)

1 year from date of purchase Warranty **Information** 

**Charging Protocols** 

NEC D720114 Charging Downstream Port (CDP), Dedicated Charging Port

(DCP)

**Hardware LED Indicators** Port Status, Power

> **Downstream USB Ports** 4 Type-A Female USB **Upstream USB Ports** 1 Type-B Female USB

**Max Data Transfer Rate** 480Mbps Performance &

Chipset

Safety **Over Current Protection** Yes

> **USB Interface USB 2.0**

**UPC** 736983900395

**Series** WKS-UH (Workstation Series Hubs) Other Data

> Weight 1.5 lbs

**Dimensions**  $11 \times 6 \times 2$  in

## Ready to Buy? Let's get to work!

Purchase order lets set you up.

Online with Credit card Orders shipped same day!

\*orders placed prior to 3:30pm EST

1-888-688-2188 (Toll free)

sales@coolgear.com