

## 7 Port USB 2.0 Hub w/ Screw Locking Ports



Industrial Grade | +7~24V DC Input | Surface Mountable | DIN Rail | 480 Mbps | Screw Lock

Model No. USBG-7DU2



- **High Speeds:** This USB hub is 2.0 compliant, ensuring fast 480Mbps data transfer speeds. It supports high speed and full speed which enables it to be compatible with USB 1.1.
- Superior Build Quality: Housed in a rugged steel chassis with built in mountable flanges, the 7-port hub is perfect for installations in offices, labs, warehouses, heavy machinery, automation equipment, and other industrial applications.
- Secure Connections: Each port features a screw locking for safe and secure USB connections.
- Upstream: 1 USB port, Type B connector, Screw-lock type
- Downstream: 7 USB ports, Type A connectors, Screw-lock type
- Power Connector: 2-Pin Terminal Block
- Mounting Options: Wall, Surface, & DIN Rail



Interested? LEARN MORE >

## **Questions?** Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

<sup>1</sup> 1-727-209-1300 (Local) **expert@coolgear.com** 



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

**Within every great machine, lives Coolgear.** - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

**Advanced Engineering** - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

# PRODUCT SPECIFICATIONS

#### Looking for product documentation?

View CAD Models, Data sheet and Drawings here >



Input Voltage +7~24V DC

**Power Source** 2-Pin Terminal Block, AC Adapter Not Included

**Power** Idle Consumption 23.82mA Bus Powered, 36.7 mA @ 12V Terminal Power

**External Power Required** No

**Charging Protocols** Dedicated Charging Port (DCP)

Country of Origin Taiwan Compliance

Certifications TAA Hubs, RoHS

**Color** Black

Item Dimensions (L × W ×

H)

 $5.2 \times 2.42 \times 1.43$  in.

Physical Item Weight 0.625 lbs.

**Characteristics** Mounting Style Surface / Wall Mount, Din-Rail Mount

Ports 7 USB Ports

Material of Construction Galvanized Steel

Screw Lock Compatible Yes

What's in the Box Package Contents

DIN Rail Clip(s), Hub, Screw Lock USB-A to Screw Lock USB-B

Cable, Screw Pack

1 year from date of purchase

**Software** OS Support OS Independent; No Additional Drivers Required

Operating Temperature 0°C to 55°C (32°F to 131°F)

Storage Temperature -20°C to 85°C (-4°F to 185°F)

Humidity 5% ~ 95% (non-condensing)

Turnatey 5/0 · 75/0 (non-condensing

Information

Chipset NEC D720113GK

**Charging Protocols** Dedicated Charging Port (DCP)

Yes

Hardware LED Indicators Power

Warranty

**Downstream USB Ports** 7 Type-A Female USB **Upstream USB Ports** 1 Type-B Female USB

Performance &

**Environmental** 

**Product** 

Safety Over Current Protection

Max Data Transfer Rate 480Mbps

Over Voltage Protection Yes per buck

USB Interface USB 2.0

**UPC** 736983901422

Other Data Series <u>DRS-UH (DIN-Rail Series Hubs)</u>

Weight 1.15 lbs

**Dimensions**  $11 \times 6.25 \times 2 \text{ in}$ 

### Ready to Buy? Let's get to work!

Purchase order lets set you up.

1-888-688-2188 (Toll free)