



# 7 Port USB 2.0 Slim Powered Hub w/ Power Adapter



Industrial Grade | +5V DC Input | Surface Mountable | 480 Mbps

Model No. USBG-7U2ML



- **High Speeds:** This USB hub is 2.0 compliant, ensuring fast 480Mbps data transfer speeds. It supports high speed and full speed which enables it to be compatible with USB 1.1.
- **Superior Build Quality:** Housed in a rugged steel chassis with built in mountable flanges, the 7-port hub is perfect for installations in offices, labs, warehouses, heavy machinery, automation equipment, and other industrial applications.
- **Power Your Way:** The 7-port hub works in either bus-powered mode or self-powered mode with the included power adapter.
- **Upstream:** 1 USB port, Type B connector
- **Downstream:** 7 USB ports, Type A connectors
- **Power Connector:** DC Barrel Jack, 4-Pin Aux Power Connector
- **Mounting Options:** Wall & Surface



[View more images here >](#)

**Interested? LEARN MORE →**

## Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

☎ [1-727-209-1300](tel:1-727-209-1300) (Local) ✉ [expert@coolgear.com](mailto:expert@coolgear.com)



**We Speak Your Speak** - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

**We're Ready For Integration, Every Time.** - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

**Within every great machine, lives Coolgear.** - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

**Advanced Engineering** - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

# PRODUCT SPECIFICATIONS

Looking for product documentation?

[View CAD Models, Data sheet and Drawings here >](#)



Power	<b>Input Voltage</b>	+5V DC
	<b>Power Source</b>	4-Pin Aux Power Connector, AC Adapter Included, DC Barrel Jack 2.5mm ID × 5.5mm OD
	<b>Idle Consumption</b>	3.26mA Bus Powered, 3.63mA @ 5V Terminal Power
	<b>Adapter Input Current</b>	0.58A
	<b>Adapter Input Voltage</b>	100~240V AC
	<b>Adapter Output Current</b>	4A
	<b>Adapter Output Voltage</b>	5V DC
	<b>External Power Required</b>	No
Compliance	<b>Charging Protocols</b>	Dedicated Charging Port (DCP)
	<b>Per USB Port Current</b>	1.5 A
	<b>Country of Origin</b>	Taiwan
	<b>Certifications</b>	<a href="#">RoHS</a>
	<b>Color</b>	Black
Physical Characteristics	<b>Item Dimensions (L × W × H)</b>	6.01 (7.01 w/flange) × 2.35 × 0.91 in.
	<b>Item Weight</b>	0.612 lbs.
	<b>Mounting Style</b>	Surface / Wall Mount
	<b>Ports</b>	7 USB Ports
What's in the Box	<b>Material of Construction</b>	Galvanized Steel
	<b>Package Contents</b>	Hub, Power Adapter, USB-A to USB-B Cable
Software	<b>OS Support</b>	Win 11, Linux, Mac OSX, Win 10, Win 7, Win 8
Environmental	<b>Operating Temperature</b>	0°C to 55°C (32°F to 131°F)
	<b>Storage Temperature</b>	-20 to 75°C (-4 to 167°F)
	<b>Humidity</b>	5% ~ 95% (non-condensing)
Product Information	<b>Warranty</b>	1 year from date of purchase
Hardware	<b>Chipset</b>	FE2.1
	<b>LED Indicators</b>	Power
	<b>Downstream USB Ports</b>	7 Type-A Female USB
	<b>Upstream USB Ports</b>	1 Type-B Female USB
Performance & Safety	<b>Max Data Transfer Rate</b>	480Mbps
	<b>USB Interface</b>	USB 2.0
Other Data	<b>UPC</b>	729440625139
	<b>Series</b>	<a href="#">WKS-UH (Workstation Series Hubs)</a>
	<b>Weight</b>	1.8 lbs
	<b>Dimensions</b>	11.5 × 7.5 × 2.75 in

**Ready to Buy? Let's get to work!**

**Purchase order** lets set you up.

**Online with Credit card** Orders shipped same day!

\*orders placed prior to 3:30pm EST

☎ **1-888-688-2188 (Toll free)**

✉ **sales@coolgear.com**