

# 12 Port Industrial USB 3.2 Gen 1 Hub w/ Port Status LEDs



Industrial Grade | +9~30V DC Input | Surface Mountable | 5 Gbps | LED Indicators

Model No. USBG-12U3ML





- Super Fast Speeds: This USB hub is 3.2 Gen 1 compliant, ensuring super-fast 5Gbps data transfer speeds. It supports super speed, high speed and full speed which enables it to be compatible with USB 2.0 / 1.1.
- Superior Build Quality: Housed in a rugged steel chassis with built in mountable flanges, the 12-port hub is perfect for installations in offices, labs, warehouses, heavy machinery, automation equipment, and other industrial applications.
- Check Your Ports' Status: Quickly check the status of each port individually with built in LED indicators.
- Upstream: 1 USB port, Type B connector
- Downstream: 12 USB ports, Type A connectors
- Power Connector: 3-Pin Terminal Block
- Mounting Options: Wall & Surface
- Supply Current: 900mA USB Bus Power for Each Downstream Port

Interested? LEARN MORE >

## **Questions?** Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

<sup>1</sup> 1-727-209-1300 (Local) **expert@coolgear.com** 



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

**Within every great machine, lives Coolgear.** - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

**Advanced Engineering** - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

#### **PRODUCT SPECIFICATIONS**

#### Looking for product documentation?

View CAD Models, Data sheet and Drawings here >



**Input Voltage** +9~30V DC

**Power Source** 3-Pin Terminal Block, AC Adapter Not Included

**Idle Consumption** 18.72mA @ 12V Terminal Power **Power** 

**External Power Required** Yes

**Charging Protocols** Charging Downstream Port (CDP)

**Per USB Port Current** 900mA maximum

**Country of Origin** Taiwan Compliance

Certifications RoHS, TAA Hubs

Color Black

Item Dimensions (L × W ×

H)

 $5.13 \times 2.61 \times 2.03$  in.

**Physical** 

**Characteristics** 

0.825 lbs. **Item Weight** 

**Mounting Style** Surface / Wall Mount, Din-Rail Mount

12 USB Ports Material of Construction Galvanized Steel

What's in the Box Package Contents 3-Pin Terminal Block, Hub, Screw Pack, USB-A to USB-B Cable

**Software OS Support** Win 7, Win 8, Win 10, Win 11, Linux, Mac OSX

**Operating Temperature** 0°C to 55°C (32°F to 131°F)

-20°C to 85°C (-4°F to 185°F) Environmental **Storage Temperature** 

> 5% ~ 95% (non-condensing) Humidity

**Product** 

Warranty 1 year from date of purchase **Information** 

> Chipset GL 3522

Port Status, Power **LED Indicators Hardware** 

**Downstream USB Ports** 12 Type-A Female USB

5Gbps

**Upstream USB Ports** 1 Type-B Female USB

Performance &

Safety

**Max Data Transfer Rate** 

**Over Current Protection** Yes

Over Voltage Protection Yes per buck

**USB** Interface USB 3.2 Gen 1 **UPC** 729440692100

**Other Data** DRS-UH (DIN-Rail Series Hubs) **Series** 

> Weight 1.25 lbs

**Dimensions**  $8.5 \times 5.5 \times 2.5$  in

### Ready to Buy? Let's get to work!

Purchase order lets set you up.

Online with Credit card Orders shipped same day!

sales@coolgear.com

<sup>1</sup> 1-888-688-2188 (Toll free)

\*orders placed prior to 3:30pm EST

