

12 Port Industrial USB 3.2 Gen 1 Hub w/ Port Status LEDs



Industrial Grade | +9~30V DC Input | Surface Mountable | 5 Gbps | LED Indicators

Model No. USBG-12U3ML





- Super Fast Speeds: This USB hub is 3.2 Gen 1 compliant, ensuring super-fast 5Gbps data transfer speeds. It supports super speed, high speed and full speed which enables it to be compatible with USB 2.0 / 1.1.
- Superior Build Quality: Housed in a rugged steel chassis with built in mountable flanges, the 12-port hub is perfect for installations in offices, labs, warehouses, heavy machinery, automation equipment, and other industrial applications.
- Check Your Ports' Status: Quickly check the status of each port individually with built in LED indicators.
- Upstream: 1 USB port, Type B connector
- Downstream: 12 USB ports, Type A connectors
- Power Connector: 3-Pin Terminal Block
- Mounting Options: Wall & Surface
- Supply Current: 900mA USB Bus Power for Each Downstream Port

Interested? LEARN MORE >

Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

¹ 1-727-209-1300 (Local) **expert@coolgear.com**



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS

Looking for product documentation?

View CAD Models, Data sheet and Drawings here >



Input Voltage +9~30V DC

Power Source 3-Pin Terminal Block, AC Adapter Not Included

Power 18.72mA @ 12V Terminal Power

External Power Required Yes

Charging Protocols Charging Downstream Port (CDP)

Per USB Port Current 900mA maximum

Country of Origin Taiwan Compliance

Certifications TAA Hubs, RoHS

Color Black

Item Dimensions (L × W ×

5.13 × 2.61 × 2.03 in.

Physical Item Weight 0.825 lbs.

H)

Product

Mounting Style Surface / Wall Mount, Din-Rail Mount

Ports 12 USB Ports

Material of Construction Galvanized Steel

What's in the Box Package Contents 3-Pin Terminal Block, Hub, Screw Pack, USB-A to USB-B Cable

Software OS Support Win 11, Linux, Mac OSX, Win 10, Win 7, Win 8

Operating Temperature 0°C to 55°C (32°F to 131°F)

Environmental Storage Temperature -20°C to 85°C (-4°F to 185°F)

Humidity 5% ~ 95% (non-condensing)

Information 1 year from date of purchase

Chipset GL 3522

Charging Protocols Charging Downstream Port (CDP)

Hardware LED Indicators Port Status, Power

Downstream USB Ports 12 Type-A Female USB **Upstream USB Ports** 1 Type-B Female USB

Performance & Max Data Transfer Rate 5Gbps
Over Current Protection Yes

Over Voltage Protection Yes per buck

USB Interface USB 3.2 Gen 1 **UPC** 729440692100

Other Data Series DRS-UH (DIN-Rail Series Hubs)

Weight 1.25 lbs

Dimensions $8.5 \times 5.5 \times 2.5 \text{ in}$

Ready to Buy? Let's get to work!

Purchase order lets set you up.

Online with Credit card Orders shipped same day!

1-888-688-2188 (Toll free)