




Single Port USB 2.0 to RS-422 / RS-485 DB-9 Serial Adapter



RS-422 | RS-485 | 128 Bytes Receive | 256 Bytes Transmit | FTDI

Model No. USB-COMi



- **Expand Your Serial Capabilities:** The Mini Serial Adapter can be utilized through an existing USB Port to work with your legacy serial connections. It's great for newer technologies with no serial port connections.
- **Safe Connections:** Designed with a unique system load reduction feature, the USB to Serial Adapter also offers 15kV surge protection for connected devices.
- **Upstream:** 1 USB port, Type B Female Connector
- **Downstream:** 1 Male DB9, w/ nuts
- **RS-422 Signals:** TxD-, TxD+, RxD+, RxD-, GND, RTS-, RTS+, CTS+, CTS-
- **RS-485 Signals:** TxD-, TxD+, RxD+, RxD-, GND
- **Transmit Buffer:** 256 Bytes
- **Receive Buffer:** 128 Bytes

Interested? [LEARN MORE](#) →



[View more images here >](#)

Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

☎ [1-727-209-1300](tel:1-727-209-1300) (Local) ✉ expert@coolgear.com



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS

Looking for product documentation?
[View CAD Models, Data sheet and Drawings here >](#)



Power	Adapter Power	USB Bus Powered
	Power Source	USB Connector
	External Power Required	No
Compliance	Country of Origin	Taiwan
	Color	Blue/Gray
Physical Characteristics	Item Dimensions (L x W x H)	3.30 x 2.87 x 1.62 in.
	Item Weight	0.181 lbs.
	Ports	1 Serial Port
	Material of Construction	Plastic
	Screw Lock Compatible	Yes
Serial Attributes	RS Signals	TxD-, TxD+, RxD+, RxD-, GND, TxD-, TxD+, RxD+, RxD-, GND, RTS-, RTS+, CTS+, CTS-
	Serial Standards	RS422, RS485
	Baud Rate	921.6K bps
	FIFO Receive	128 bytes
	FIFO Transmit	256 bytes
	Data Bits	7, 8
	Parity	None, Even, Odd, Mark, Space
	Stop Bits	1, 2
	Flow Control	Hardware (RTS, CTS), XON/XOFF
	OS Support	Win 7, Win 8, Win 10, Win 11, Linux, Mac OSX
Environmental	Operating Temperature	0°C to 55°C (32°F to 131°F)
	Storage Temperature	-20 to 75°C (-4 to 167°F)
	Humidity	5% ~ 95% (non-condensing)
Product Information	Warranty	1 year from date of purchase
Hardware	Chipset	FTDI
	LED Indicators	TX / RX
Performance & Safety	ESD Protection	15KV Surge Protection
	Max Data Transfer Rate	12Mbps
Other Data	Connector	DB9 Male w/ Nuts
	Chip Model	FT231XQ-R, MAX3089E
	USB Interface	USB 2.0
	Weight	.65 lbs
	Dimensions	4 x 4 x 2.5 in

Ready to Buy? Let's get to work!

Purchase order lets set you up.

Online with Credit card Orders shipped same day!

*orders placed prior to 3:30pm EST

☎ **1-888-688-2188 (Toll free)**

✉ **sales@coolgear.com**