



# USB 2.0 to 4 Port RS-232 Serial Adapter Optical isolated



USB to RS232 Serial Adapter

Model No. USB2-4COM-SI-M



USB 2.0 Serial Adapter with Optical isolation and surge protection is available on each serial port and is individually optically isolated with 2000 volt DC optical isolation on 8 signal pins. Meets the highest level of optical isolation protecting your computer from spikes and surges.

- Incorporates Optical Isolation and Surge Protection over each port.
- Connects to a Host USB system port or USB Hub via USB cable
- Provides high speed serial port baud rate at 921.6Kbps
- Installed as a standard Windows COM port to communicate with Factory Automation, Bar Code Scanners, Time Clocks or other.

Interested? [LEARN MORE](#) →



[View more images here >](#)

## Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

☎ [1-727-209-1300](tel:1-727-209-1300) (Local) ✉ [expert@coolgear.com](mailto:expert@coolgear.com)



**We Speak Your Speak** - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

**We're Ready For Integration, Every Time.** - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

**Within every great machine, lives Coolgear.** - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

**Advanced Engineering** - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

# PRODUCT SPECIFICATIONS

Looking for product documentation?

[View CAD Models, Data sheet and Drawings here >](#)




<b>Compliance</b>	<b>Country of Origin</b>	Taiwan
	<b>Certifications</b>	<a href="#">CE</a> , <a href="#">FCC</a>
	<b>Color</b>	White
<b>Physical Characteristics</b>	<b>Mounting Style</b>	Din-Rail (Optional Bracket)
	<b>Ports</b>	4 Serial Ports
	<b>Screw Lock Compatible</b>	Yes
<b>Serial Attributes</b>	<b>Serial Standards</b>	RS232
<b>Software</b>	<b>OS Support</b>	Linux, Win 10, Win 7, Win 8, Win Vista, Win XP
<b>Environmental</b>	<b>Operating Temperature</b>	0C to 55C
<b>Hardware</b>	<b>Chipset</b>	FTDI
<b>Performance &amp; Safety</b>	<b>Isolated/Surge Protected</b>	Yes
	<b>Connector</b>	DB9 Male w/ Nuts
<b>Other Data</b>	<b>Chip Model</b>	FT4232HL, ZT213LFEA
	<b>Weight</b>	3.0 lbs

## Ready to Buy? Let's get to work!

[Purchase order](#) lets set you up.

[Online with Credit card](#) Orders shipped same day!

\*orders placed prior to 3:30pm EST

 [1-888-688-2188 \(Toll free\)](tel:1-888-688-2188)

 [sales@coolgear.com](mailto:sales@coolgear.com)