



Single Port Industrial Adapter USB 2.0 to RS-232 / 422 / 485 w/ FTDI Chip



Model No. USB-COMiPLUS



RS-232 | 384 Bytes Receive | 128 Bytes Transmit | FTDI

- **Expand Your Serial Capabilities:** Connect your legacy 9-pin serial device through a USB-A port to add legacy functionality to newer technologies with no serial port connections.
- **Safe Connections:** Designed with a unique system load reduction feature, the Mini USB to Serial Adapter also offers 15kV surge protection for connected devices.
- **Plug-&-Play:** The adapter's power is drawn from a USB connection for ease of access and is compatible with Windows (up to Win 11), Mac OS, and Linux.
- **Effortless Port Configuration:** The adapter is designed with external dip switches to set RS-232, RS-422 or RS-485 ports and different operation modes conveniently.
- **COM Retention:** COM Ports are fully configurable, and after reboots, port assignments are preserved.
- **Upstream:** 1 USB port, Type A Male Connector
- **Downstream:** 1 Male DB9, w/ nuts

Interested? [LEARN MORE](#) →

Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

☎ [1-727-209-1300](tel:1-727-209-1300) (Local) ✉ expert@coolgear.com



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This

means greater duty cycle, zero data loss, and longer lasting builds. We promise.,
Coolgear | Charging & Connectivity Experts Visit coolgear.com/support for any questions & inquires.
www.coolgear.com

PRODUCT SPECIFICATIONS

Looking for product documentation?
[View CAD Models, Data sheet and Drawings here >](#)



Power	External Power Required	No	
Physical Characteristics	Color	Black/White	
	Ports	1 Serial Port	
	Material of Construction	Plastic	
	Screw Lock Compatible	Yes	
	RS Signals	TxD, RxD, RTS, CTS, DSR, DTR, DCD, RI, GND	
Serial Attributes	Serial Standards	RS232, RS422, RS485	
	FIFO Receive	384 bytes	
	FIFO Transmit	128 bytes	
	Data Bits	5, 6, 7, 8	
	Parity	None, Even, Odd, Mark, Space	
	Stop Bits	1, 1.5, 2	
	Flow Control	Hardware (RTS, CTS), XON/XOFF	
	Serial Ports	1	
	Software	OS Support	Win 11, Linux, Mac OSX, Win 10, Win 7, Win 8
	Environmental	Operating Temperature	0°C to 55°C (32°F to 131°F)
Storage Temperature		-20 to 75°C (-4 to 167°F)	
Humidity		5% ~ 95% (non-condensing)	
Product Information	Warranty	1 year from date of purchase	
Hardware	Chipset	FTDI	
Performance & Safety	ESD Protection	15KV Surge Protection	
	Isolated/Surge Protected	Yes	
	Chip Model	FT232RL, MAX3089E, ZT213LFEA	
Other Data	Connector	DB9 Male w/ Nuts	
	USB Interface	USB 2.0	
	Weight	.4 lbs	
	Dimensions	4 × 4 × 2.25 in	

Ready to Buy? Let's get to work!

Purchase order lets set you up.

Online with Credit card Orders shipped same day!

*orders placed prior to 3:30pm EST

☎ **1-888-688-2188 (Toll free)**

✉ **sales@coolgear.com**