

4 Port USB 3.2 Gen 1 Hub w/ Screw-Locking Ports & Status LEDs



Industrial Grade | +7~24V DC Input | Surface Mountable | 5 Gbps | LED Indicators

Model No. USBG-3X4M





- Super Fast Speeds: This USB hub is 3.2 Gen 1 compliant, ensuring super-fast 5Gbps data transfer speeds. It supports super speed, high speed and full speed which enables it to be compatible with USB 2.0 / 1.1.
- Superior Build Quality: Housed in a rugged steel chassis with built in mountable flanges, the 4-port hub is perfect for installations in offices, labs, warehouses, heavy machinery, automation equipment, and other industrial applications.
- Check Your Ports' Status: Quickly check the status of each port individually with built in LED indicators.
- Upstream: 1 USB port, Type B connector, Screw-lock type
- Downstream: 4 USB ports, Type A connectors, Screw-lock type
- Power Connector: 2-Pin Terminal Block, DC Barrel 2.1mm
 ID × 5.5mm OD
- Mounting Options: Wall & Surface
- Supply Current: 900mA USB Bus Power for Each Downstream Port

Interested? LEARN MORE →

Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

1-727-209-1300 (Local) expert@coolgear.com



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS

Looking for product documentation?

View CAD Models, Data sheet and Drawings here >



Input Voltage +7~24V DC

2-Pin Terminal Block, AC Adapter Included, DC Barrel Jack

2.1mm ID x 5.5mm OD

Idle Consumption 17.27 mA @ 12V Terminal Power, 38mA Bus Powered

Adapter Input Current 1A

Adapter Input Voltage 100~240V AC

Adapter Output Current 3A
Adapter Output Voltage 12V DC

External Power Required No

Charging Protocols

Charging Downstream Port (CDP), Dedicated Charging Port

(DCP)

Per USB Port Current 900mA maximum

Compliance Certifications TAA Hubs, RoHS

Color Black

Item Dimensions (L × W ×

H)

 $7.02 \times 2.34 \times 0.91$ in.

Physical Item Weight 0.650 lbs.

Characteristics Mounting Style Surface / Wall Mount

Ports 4 USB Ports

Material of Construction Galvanized Steel

Screw Lock Compatible Yes

What's in the Box Package Contents

2-Pin Terminal Block, Hub, Power Adapter, USB-A to USB-B

Cable

Software OS Support Win 11, Linux, Mac OSX, Win 10, Win 7, Win 8

Operating Temperature 0°C to 55°C (32°F to 131°F)

Environmental Storage Temperature -20°C to 85°C (-4°F to 185°F)

Humidity 5% ~ 95% (non-condensing)

Product

Warranty 1 year from date of purchase

Chipset VL811-Q8P

LED Indicators Port Status, Power

Downstream USB Ports 4 Type-A Female USB **Upstream USB Ports** 1 Type-B Female USB

Performance &

Safety

Max Data Transfer Rate 5Gbps

USB Interface USB 3.2 Gen 1 **UPC** 045079162303

Other Data Series <u>WKS-UH (Workstation Series Hubs)</u>

Weight 1.85 lbs

Dimensions $11.25 \times 6.25 \times 2$ in

Ready to Buy? Let's get to work!

Purchase order lets set you up.

Online with Credit card Orders shipped same day!

*orders placed prior to 3:30pm EST

1-888-688-2188 (Toll free)

sales@coolgear.com