



4 Port USB 3.2 Gen 1 Powered Hub w/ ESD Surge Protection



Industrial Grade | +7~48V DC Input | Surface Mountable | DIN Rail | 5 Gbps | LED Indicators

Model No. USBG-4U3MLR2



[View more images here >](#)

- **Protect Your Equipment:** The 4-port USB 3.2 Gen 1 features 15kV ESD surge protection per port to keep your connected peripherals safe from harm.
- **Super Fast Speeds:** This USB hub is 3.2 Gen 1 compliant, ensuring super-fast 5Gbps data transfer speeds. It supports super speed, high speed and full speed which enables it to be compatible with USB 2.0 / 1.1.
- **Superior Build Quality:** Housed in a rugged steel chassis with built in mountable flanges, the 4-port hub is perfect for installations in offices, labs, warehouses, heavy machinery, automation equipment, and other industrial applications.
- **Upstream:** 1 USB port, Type B connector
- **Downstream:** 4 USB ports, Type A connectors
- **Power Connector:** 2-Pin Terminal Block
- **Mounting Options:** Wall, Surface, and DIN Rail
- **Supply Current:** 900mA USB Bus Power for Each Downstream Port

Interested? [LEARN MORE >](#)

Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

☎ [1-727-209-1300](tel:1-727-209-1300) (Local) ✉ expert@coolgear.com



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS

Looking for product documentation?

[View CAD Models, Data sheet and Drawings here >](#)



Power	Input Voltage	+7~48V DC
	Power Source	2-Pin Terminal Block, AC Adapter Not Included
	Idle Consumption	7mA @ 12V Terminal Power, 9.4mA Bus Powered
	External Power Required	No
	Charging Protocols	BC 1.2, Charging Downstream Port (CDP)
	Per USB Port Current	900mA maximum
Compliance	Country of Origin	Taiwan
	Certifications	REACH , RoHS , TAA
	Color	Black
Physical Characteristics	Item Dimensions (L x W x H)	4.50 x 2.26 x 1.03 in.
	Item Weight	0.431 lbs.
	Mounting Style	Surface / Wall Mount, Din-Rail Mount
	Ports	4 USB Ports
	Material of Construction	Galvanized Steel
	What's in the Box	Package Contents
Software	OS Support	Win 7, Win 8, Win 10, Win 11, Linux, Mac OSX
Environmental	Operating Temperature	0°C to 55°C (32°F to 131°F)
	Storage Temperature	-20°C to 85°C (-4°F to 185°F)
	Humidity	5% ~ 95% (non-condensing)
Product Information	Warranty	1 year from date of purchase
Hardware	Chipset	GL 3523
	LED Indicators	Power
	Downstream USB Ports	4 Type-A Female USB
	Upstream USB Ports	1 Type-B Female USB
	ESD Protection	15KV Surge Protection for Each Port
	Isolated/Surge Protected	Yes
Performance & Safety	Max Data Transfer Rate	5Gbps
	Over Current Protection	Yes
	Over Voltage Protection	Yes per buck
	USB Interface	USB 3.2 Gen 1
Other Data	UPC	736983900173
	Series	DRS-UH (DIN-Rail Series Hubs)
	Weight	1.243 lbs
	Dimensions	9.000 x 6.625 x 1.625 in

Ready to Buy? Let's get to work!

1-888-688-2188 (Toll free)

Purchase order lets set you up.

Coolgear | Charging & Connectivity Experts
www.coolgear.com

Visit coolgear.com/support for any questions & inquiries.

Online with Credit card Orders shipped same day!

✉ sales@coolgear.com

*orders placed prior to 3:30pm EST