

4 Port USB 3.2 Gen 1 Mini Powered Hub w/ ESD Surge Protection & Power Adapter



Industrial Grade | +5V DC Input | Surge Protection | Surface Mountable | 5 Gbps

Model No. CG-U3MINI4PH





- Protect Your Equipment: The 4-port hub features 15kV ESD surge protection to keep your connected peripherals safe from harm.
- Super Fast Speeds: This USB hub is 3.2 Gen 1 compliant, ensuring super-fast 5Gbps data transfer speeds. It supports super speed, high speed and full speed which enables it to be compatible with USB 2.0 / 1.1.
- Small-Scale Quality: Housed in a compact steel chassis, the 4-port hub is perfect for discreet installations in offices, labs, warehouses, heavy machinery, automation equipment, and other industrial applications.
- Upstream: 1 USB port, Type B connector
- **Downstream:** 4 USB ports, Type A connectors
- Power Connector: DC Barrel 2.5mm ID × 5.5mm OD, Center Pin Positive
- Mounting Options: Wall & Surface

Interested? LEARN MORE >

Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

¹ 1-727-209-1300 (Local) **expert@coolgear.com**



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS

Looking for product documentation?

View CAD Models, Data sheet and Drawings here >



Input Voltage +5V DC

Power Source AC Adapter Included, DC Barrel Jack 2.5mm ID × 5.5mm OD

Idle Consumption 57mA @ 5V / 35.6mA Bus Power

Power External Power Required No

BC 1.2, Charging Downstream Port (CDP), Dedicated

Charging Protocols Charging Port (DCP), Samsung, Standard Downstream Port

(SDP)

Per USB Port Current 2A

Country of Origin

H)

China

Certifications RoHS

Color Black

Item Dimensions (L × W ×

 $2.87 (3.81 \text{ with flanges}) \times 1.86 \times 1.13 \text{ in.}$

Physical

Characteristics Item Weight 0.32 lbs.

Mounting Style Surface / Wall Mount

Ports 4 USB Ports

Material of Construction Galvanized Steel

What's in the Box Package Contents Hub, Power Adapter, USB-A to USB-B Cable

Software OS Support Win 7, Win 8, Win 10, Win 11, Linux, Mac OSX

Operating Temperature 0°C to 55°C (32°F to 131°F)

Environmental Storage Temperature -20 to 75°C (-4 to 167°F)

Humidity 5% ~ 95% (non-condensing)

Product

Warranty 1 year from date of purchase

Chipset GL3510

Hardware Downstream USB Ports 4 Type-A Female USB

Upstream USB Ports 1 Type-B Female USB

ESD Protection 15KV Surge Protection for Each Port

Isolated/Surge Protected Yes

Performance & Max Data Transfer Rate 5Gbps

Safety Over Current Protection Yes

Over Voltage Protection Yes per buck

Surge Protection 350W

USB Interface USB 3.2 Gen 1 **UPC** 045079158399

Other Data Series <u>WKS-UH (Workstation Series Hubs)</u>

Weight 0.75 lbs

Dimensions $5.25 \times 4.50 \times 1.500 \text{ in}$

Purchase order lets set you up.

Online with Credit card Orders shipped same day!

*orders placed prior to 3:30pm EST

1-888-688-2188 (Toll free)

sales@coolgear.com