



4 Port USB 3.2 Gen 1 Type-C Hub w/ ESD Surge Protection & Type-C Upstream



Industrial Grade | +7~48V DC Input | Surface Mountable | DIN Rail | 5 Gbps | Screw Lock

Model No. CG-4PU31C2P



- **Protect Your Equipment:** The 4-port Type-C hub supports 15KV ESD surge protection for each port to keep your connected peripherals safe from harm.
- **Super Fast Speeds:** This USB hub is 3.2 Gen 1 compliant, ensuring super-fast 5Gbps data transfer speeds. It supports super speed, high speed and full speed which enables it to be compatible with 2.0 / 1.1.
- **Superior Build Quality:** Housed in a rugged steel chassis with built in mountable flanges, the 4-port hub is perfect for workstations installations in offices, labs, warehouses, and other industrial applications.
- **Upstream:** 1 USB port, Type C connector
- **Downstream:** 1 USB ports, Type C connectors & 3 USB ports, Type A connectors
- **Power Connector:** 2-Pin Terminal Block
- **Mounting Options:** Wall, Surface, & DIN Rail

Interested? [LEARN MORE](#) →

Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

☎ [1-727-209-1300](tel:1-727-209-1300) (Local) ✉ expert@coolgear.com



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS

Looking for product documentation?

[View CAD Models, Data sheet and Drawings here >](#)



Power	Input Voltage	+7~48V DC
	Power Source	2-Pin Terminal Block, AC Adapter Not Included
	Idle Consumption	11.45mA Bus Powered, 6.37mA @ 12V Terminal Power
	External Power Required	No
Compliance	Charging Protocols	Apple 2.4A, Charging Downstream Port (CDP), Dedicated Charging Port (DCP)
	Country of Origin	Taiwan
	Color	Black
Physical Characteristics	Item Dimensions (L x W x H)	4.50 x 2.26 x 1.03 in.
	Item Weight	0.413 lbs.
	Mounting Style	Surface / Wall Mount, Din-Rail Mount
	Ports	4 USB Ports
	Material of Construction	Galvanized Steel
	What's in the Box	Package Contents
Software	OS Support	Win 11, Linux, Mac OSX, Win 10, Win 7, Win 8
Environmental	Operating Temperature	0°C to 55°C (32°F to 131°F)
	Storage Temperature	-20°C to 85°C (-4°F to 185°F)
	Humidity	5% ~ 95% (non-condensing)
Product Information	Warranty	1 year from date of purchase
	Chipset	GL 3523
Hardware	Charging Protocols	Apple 2.4A, Charging Downstream Port (CDP), Dedicated Charging Port (DCP)
	LED Indicators	Power
	Downstream USB Ports	1 Type-C Female USB, 3 Type-A Female USB
	Upstream USB Ports	1 Type-C Female USB
	ESD Protection	15KV Surge Protection for Each Port
	Isolated/Surge Protected	Yes
Performance & Safety	Max Data Transfer Rate	5Gbps
	Over Current Protection	Yes
	Over Voltage Protection	Yes per buck
	USB Interface	USB 3.2 Gen 1
	Connector	USB Type-A Female, USB Type-C Female
Other Data	UPC	045079158405
	Series	DRS-UH (DIN-Rail Series Hubs)
	Weight	0.793 lbs
	Dimensions	9.625 x 6.625 x 2.125 in

Ready to Buy? Let's get to work!

Purchase order lets set you up.

Online with Credit card Orders shipped same day!

*orders placed prior to 3:30pm EST

☎ **1-888-688-2188 (Toll free)**

✉ **sales@coolgear.com**