

**P:** +1-727-209-1300 F: +1-727-209-1302 coolgear.com



**Technical Data Sheet Rev 05.240702** 

# 20 Port USB-C 3.2 Gen 1 Industrial Power Delivery Charging **Hub w/ ESD Surge Protection & Port Status LEDs**

Model Number: CG-20XU3CPD









### **Features**

- Simultaneous Charging: Charge and sync up to 20 iPads, iPhones or other USB-charged in charge mode devices
- Protect Your Equipment: Hub features 15kV ESD protection to keep your connected peripherals safe
- High Speeds: This USB hub is 3.2 Gen 1 compliant, ensuring super-fast 5Gbps data transfer speeds
- · Superior Build Quality: Housed in a rugged metal chassis
- Power Connector: 2x 6-Pin Molex Power Connectors

### **Package Contents**

- Hub
- Mounting Bracket
- Power Cable
- Power Supply
- Screw Pack
- USB Cable

| OVERVIEW               |                             |
|------------------------|-----------------------------|
| Model No               | CG-20XU3CPD                 |
| Product Type           | USB Hub                     |
| Compliance             | RoHS                        |
| UPC                    | 045079164635                |
| Country of Origin      | Taiwan                      |
| LED indicators         | Port Status   Power         |
| Chipset                | FE 1.1s                     |
| Electrical Protections | ±15kV (air), ±8kV (contact) |

### **PHYSICAL**

| Ship Weight (lbs) | 7.5 lbs                              |
|-------------------|--------------------------------------|
| Ship Weight (kg)  | 3.4 kg                               |
| Material          | Steel                                |
| Color             | Black                                |
| Mountable         | Desktop   Surface Mount   Wall Mount |





## Specifications Cont.

| opecifications cont.        |   |  |
|-----------------------------|---|--|
| CONNECTIONS                 |   |  |
| USB Specification           | USB 3.2 Gen 1   |  |
| Maximum Data Rate           | 5 Gbps  |  |
| Downstream Port Count       | 20  |  |
| Downstream Port Type        | 20x Type C USB 3.2 G1 / 3.0 PD  |  |
| Works as Standalone Charger | Y - Can be used without Host  |  |
| Can be Bus Powered          | N - External Power Required   |  |
| Power                       |   |  |
| Input Voltage               | 19V DC  |  |
| Supported Charge Protocols  | Apple Charge 2.4A   BC 1.2   CDP   DCP  |  |
| ENVIRONMENTAL               |   |  |
| Operating Temperature       | 0C ~ 40C  |  |
| Storage Temperature         | 0C ~ 60C  |  |
| Operating Humidity          | 0% to 80% RH  |  |
| OS SUPPORT                  |   |  |
| Supported Operating Systems | Linux   OSX 10   Windows 11   Windows 10   Windows 8   Windows 7  |  |
| WARRANTY                    |   |  |
| Warranty Period             | 1 Year  |  |
| PRODUCT URL                 |   |  |
| CG-20XU3CPD Product Page    | https://www.coolgear.com/product/20-port-usb-c-2-0-industrial-high-power-charging-hub-w-esd-surge-protection-port-status-leds |  |