

Technical Data Sheet Rev 06-240719

4-Port USB 3.2 2 USB-C 2 USB-A w/ 15KV ESD Surge Protection

Model Number: CG-4P31CHUB-M



Features

- Compliant with USB 3.2 Gen 2 Specifications
- Provides 4 USB3.2 Gen 2 Downstream Facing Ports (with 2 USB-C and 2 USB-A connectors)
- Supports 10Gbps, 5Gbps, 480Mbps, 12Mbps and 1.5Mbps Speed
- Supports Wide Range Input (+7~24V DC) Self-power Mode from the DC Jack or 2-pin Terminal Blocks
- Supports Port Status LED Indicators for each Port.

Package Contents

- 2-Pin Terminal Block
- Hub
- Power Cable
- Power Supply
- Screw Lock USB Cable

Specifications

OVERVIEW

Model No	CG-4P31CHUB-M
Product Type	USB Hub
Compliance	CE FCC RoHS TAA
UPC	045079162853
Country of Origin	Taiwan
LED indicators	Power
Electrical Protections	15KV

PHYSICAL

Ship Weight (lbs)	1.51 lbs
Ship Weight (kg)	0.69 kg
Length	5.98 inches
Width	2.35 inches
Height	0.93 inches
Material	Steel
Color	Black
Mountable	Din-Rail Surface Mount Wall Mount

Specifications Cont.

CONNECTIONS

USB Specification	USB 3.2 Gen 2
Maximum Data Rate	10 Gbps
Downstream Port Count	4
Downstream Port Type	2x Type A USB 3.2 G2 2x Type C USB 3.2 G2

POWER

Input Voltage	7 ~ 24V DC
---------------	------------

ENVIRONMENTAL

Operating Temperature	0C ~ 55C
Storage Temperature	-20C ~ 75C
Operating Humidity	5% ~ 95% (non-condensing)

OS SUPPORT

Supported Operating Systems	OS independent - No software or drivers required
-----------------------------	--

WARRANTY

Warranty Period	1 Year
-----------------	--------

PRODUCT URL

Mfg Page	https://www.coolgear.com/product/port-usb-3-2-gen-2-industrial-hub-type-c-x-2-type-a-x2-with-15kv-esd-surge-protection
----------	---