

Technical Data Sheet Rev 06-240719

ChargeIT! 280W Dual USB Type-C PD Charger w/ EPR Support

Model Number: CG-PD280EPR-UM



Features

- 280W USB PD3.1 Dual Port Type C EPR 28V capable Buck-boost DC adapter
- Variable voltage input range of 12~24V DC
- Supports most PD protocols including PD3.1, PPS, QC4.0+, BC1.2, etc.
- Compatible with single and dual screw-lock USB-C cables to keep your connections secure.

Package Contents

- Charger

Specifications

OVERVIEW

Model No	CG-PD280EPR-UM
Product Type	USB Chargers
Compliance	None or N/A
UPC	045079164376
Country of Origin	China
LED indicators	None or N/A
Chipset	1962
Electrical Protections	15KV

PHYSICAL

Ship Weight (lbs)	0.61 lbs
Ship Weight (kg)	0.28 kg
Material	Steel
Color	Black
Mountable	Surface Mount Wall Mount

Specifications Cont.

CONNECTIONS

Downstream Port Count	2
Downstream Port Type	2x Type C (Charging)
Works as Standalone Charger	Y - Can be used without Host
Can be Bus Powered	N - External Power Required
Bus Power Isolation	N

POWER

Input Voltage	9 ~ 30V DC
Idle Power Draw	20mA @ 12V Terminal
Max Power Draw	240W
Max Per Port Draw	140W (5A)

ENVIRONMENTAL

Operating Temperature	0C ~ 60C
Storage Temperature	-20C ~ 70C
Operating Humidity	15 ~ 85% RH

OS SUPPORT

Supported Operating Systems	OS independent - No software or drivers required
-----------------------------	--

WARRANTY

Warranty Period	1 Year
-----------------	--------

PRODUCT URL

Mfg Page	https://www.coolgear.com/product/chargeit-mini-280w-dual-usb-type-c-pd-charger-w-epr-support
----------	---