

# USB C to RS-232 6FT Serial Adapter Black w/FTDI Chipset DB9 male

Model Number: **USBG-232MM-C**



## Features

- Connects with USB Type-C host port
- Serial port protected with surge protection of 10KV
- Powered by USB C port, no external power adapter required
- LED status indicators for TxD and RxD for easy port monitoring and diagnostic
- Uses FTDI Chipset FT231XQ

## Package Contents

- Adapter

## Specifications

### OVERVIEW

Model No	USBG-232MM-C
Product Type	USB Serial Adapter
Compliance	TAA
UPC	736983909022
Country of Origin	Taiwan
LED indicators	RX / TX
Chipset	FTDI FT231XQ
Electrical Protections	N/A

### PHYSICAL

Ship Weight (lbs)	0.26 lbs
Ship Weight (kg)	0.12 kg
Material	Plastic
Color	Black
Cable Length (ft)	6

**Specifications Cont.****CONNECTIONS**

Connector(s)	DB9 Male w/ Nuts   USB 2.0 Type A Male
--------------	--

**SERIAL SPECS**

Maximum Data Rate	1 Mbaud
Minimum Data Rate	300 baud/bps
Data Bits	7, 8
Parity	None, Even, Odd, Mark, Space
Stop Bits	1, 2
Flow Control	Hardware (RTS, CTS), XON/XOFF
FIFO	512 bytes transmit and receive
Serial Modes	RS232
RS232 Signals	DCD, RxD, TxD, DTR, GND, DSR, RTS, CTS, RI

**ENVIRONMENTAL**

Operating Temperature	0C ~ 55C
Storage Temperature	-20C ~ 75C
Operating Humidity	5% to 95% RH

**OS SUPPORT**

Supported Operating Systems	Linux   OSX 10   Windows 10   Windows 8   Windows 7
-----------------------------	---

**WARRANTY**

Warranty Period	1 Year
-----------------	--------

**PRODUCT URL**

Mfg Page	<a href="https://www.usbgear.com/usbg-232mm-c.html">https://www.usbgear.com/usbg-232mm-c.html</a>
----------	---