

Technical Data Sheet Rev 06-250318

4 Port USB-C 3.2 Gen 2 Micro Powered Hub w/ ESD Surge Protection & Power Adapter

Model Number: CG-U3CMicro4ph-G2



Features

- Extremely compact steel chassis perfect for discreet installations in offices, labs, warehouses, automation & more
- Super-fast 10Gbps data transfer speeds, backwards compatible with USB 2.0 / 1.1
- Keep connections secure with screw-locking USB Type-C ports both upstream and downstream
- Features 15kV ESD surge protection to keep your connected peripherals safe from harm
- Power Connector: DC Barrel 2.5mm ID x 5.5mm OD, Center Pin Positive

Package Contents

- Hub
- Power Supply
- Screw Lock USB Cable

Specifications

OVERVIEW

| | | | |
|--------------------------|-------------------|-------------------------------|------------------------|
| Model No | CG-U3CMICRO4PH-G2 | Product Type | USB Hub |
| Compliance | None or N/A | UPC | 045079164819 |
| Country of Origin | China | LED indicators | Activity Port Status |
| Chipset | VL822 | Electrical Protections | 15KV |

PHYSICAL

| | | | |
|--------------------------|----------------------------|-------------------------|-------------|
| Ship Weight (lbs) | 1.25 lbs | Ship Weight (kg) | 0.57 kg |
| Item Weight | 0.21 lbs | Length | 2.99 inches |
| Width | 1.91 inches | Height | 1.20 inches |
| Material | Steel | Color | Black |
| Mountable | Surface Mount Wall Mount | | |

Specifications Cont.

CONNECTIONS

| | |
|------------------------------|-------------------------------|
| USB Specification | USB 3.2 Gen 2 |
| Upstream Port Type | USB 3.2G2 / 3.0 Type-C Female |
| Maximum Data Rate | 10Gbps |
| Downstream Port Count | 4 |
| Downstream Port Type | 4x Type C USB 3.2 G2 / 3.0 |

POWER

| | |
|--------------------------|---|
| Input Voltage | 7 ~ 12V DC |
| Power Connector | DC barrel, 2.5 ID x 5.5 OD, Center Pin Positive |
| Max Per Port Draw | 3A UFP, 1.5A DFP |

ENVIRONMENTAL

| | |
|------------------------------|---------------------------|
| Operating Temperature | 0C ~ 55C |
| Storage Temperature | -20C ~ 75C |
| Operating Humidity | 5% ~ 95% (non-condensing) |

OS SUPPORT

| | |
|------------------------------------|--|
| Supported Operating Systems | Linux OSX 10 Windows 11 Windows 10 Windows 8 Windows 7 |
|------------------------------------|--|

WARRANTY

| | |
|------------------------|--------|
| Warranty Period | 1 Year |
|------------------------|--------|

PRODUCT URL

| | |
|---------------------|---|
| Product Page | https://www.coolgear.com/product/4-port-usb-c-3-2-gen-2-micro-powered-hub-w-esd-surge-protection-power-adapter |
|---------------------|---|

USB CHARGING & CONNECTIVITY EXPERTS

We Speak Your Speak



When you reach out to Coolgear support, you'll find yourself in the hands of a solution-oriented and knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

[Visit Support](#)